



Wireless Microphone Accessories

MPB-30 UHF Auto Gain Controlled Booster / Power Supply



- Optimized for the 470~960 MHz frequency range
- Provides enhanced RF stability for maximum range with complex antenna configurations
- Detects and compensates for signal-loss in long cable runs automatically by providing variable gain from 0 to 13dB (± 1 dB) when powered by 8V DC excitation voltage from a MIPRO receiver or divider and when powered independently. Designed to work with the AD-708 Antenna divider.
- Provides 8V DC power independently for internal antenna boosters when used with external power supply
- Aluminum housing provides improved heat dissipation

Specifications

Bandwidth	UHF 470~960MHz
Gain	Variable from 0-13 \pm 1dB—optimized to work with the AD-708
Noise	<2.5dB (center band)
IIP3	+18dBm (center band)
Impedance	50 Ω
Input Power	12~24V DC (min. 350mA)
Regulated Output Power	8V DC (max. 250mA)
Connectors	TNC \times 2 - 2mm DC Jack \times 1
Current Consumption	TNC \times 2 - 2mm DC Jack \times 1
Dimensions	90.3(W) \times 25(H) \times 55.4(D)mm / 3.5(W) \times 1(H) \times 2.2(D)"
Weight	100g / 3.5oz.



6655 Troost Avenue, Kansas City, MO 64131-1244
Toll Free: 877-447-9216 (P) 816-581-9103 (F) 816-581-9104
www.avlex.com