

MA-101G 2.4 GHz Personal Wireless PA System

Key Features

- Lightweight, contoured and ultra-portable design.
- Built-in 1 2.4GHz true diversity receiver module with 10 auto-scannable frequencies.
- Powerful and crystal-clear sound projection thanks to high efficiency amplifier driving a full-range speaker.
- Replaced sealed lead-acid battery to rechargeable lithium battery for improved reliability, longer life and reduced weight.
- AC and lithium rechargeable battery operation.
- Up to 10 hours of standby time per 4-hour charge.
- 3.5 mm line input accepts external MP3, iPod and CD player.
- Simple to use and can be easily carried via the built-in handle, shoulder strap, or mounted on a microphone stand.



Transmitters & Microphones


ACT-24H	Handheld Transmitter
ACT-24HC	Rechargeable Handheld Transmitter
ACT-24T	Bodypack Transmitter
ACT-24TC	Rechargeable Bodypack Transmitter
MM-107	Supercardioid Dynamic Microphone

Accessories

MB-25	Lithium Rechargeable Battery (14.8 V / 2.6 AH)
SC-10	Storage and Carry Bag
MS-30	Tripod Microphone Stand

Technical Specifications

Portable PA	
Max. Power Output	50 Watts
Amplifier	Class D
Sensitivity	Typical: 95 dB Maximum: 107 dB
T.H.D.	< 1%
Frequency Response	20 Hz – 20 kHz
Loudspeaker	5" full-range, high efficiency
Audio Inputs	Wired: 6.3 mm (1/4") Line-In: 3.5 mm (1/8")
Audio Output	3.5mm (1/8")
Installation	Microphone stand, table mounted, shoulder belt.
Power Supply	AC: External 100 – 240 V AC switching power supply (Max. Power Consumption: 60 W) DC & Battery: 14.8 V / 2.6 AH rechargeable lithium battery (MB-25)
Charge Time	4 hours (automatic charging management)
Standby Time	> 10 hours
Battery Indicator	Single LED indicator
Color	Black
Dimensions (W×H×D)	160 × 178 × 285 mm / 6.3 × 7 × 11.2 "
Weight (battery included)	Approx. 2.2 kg / 4.8 lbs
Wireless System	
Receiver Channel	2.4 GHz, Single
Frequency Range	2,400 – 2,483.5 MHz
Bandwidth	83.5 MHz
Preset Channel	10
Channel Set-up	Scan & ACT sync
Antenna	Built-in



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw