ACT-24R 2.4 GHz Tour Guide Receiver

Key Features

- Industry's most compact and smallest housing. Featuring a lightweight and rugged plastic case to meet professional requirements.
- Stable digital FSK modulation circuitry. All frequencies are located in this band.
- Employ Frequency Hopping Spread Spectrum technology, and each channel presets 4 hopping frequencies that skip the Wi-Fi frequency in use.
- The adaptive tracking algorithm helps effectively avoid interference from 2.4GHz communication products.

 Dual tuner true diversity receiving technology eliminates signal dropout.
- Backlit graphic LCD screen display various function settings.
- The included battery of the rechargeable handheld and bodypack transmitters can be easily removed
- An affordable price for consumers. Ideal for guided tours, camcorders and wireless application of the sound systems.

Transmitters

ACT-24HC	Digital Handheld Transmitter
ACT-24TC	Digital Bodypack Transmitter
MT-24A	Digital Interlinking Transmitter

Technical Specifications

Housing	Rugged and compact plastic housing
Frequency Band & Modulation	ISM 2.4GHz. Digital modulation.
Frequency Range	2,400 ~ 2,483.5 MHz
Bandwidth	83 MHz
Preset Channels	12 selectable channels
Receiving Mode	Digital true diversity
Latency	< 4.0 ms
Dynamic Range	> 106 dBA
T.H.D	< 0.1%
Dimensions (W × H × D)	63 × 70 × 25 mm / 2.5 × 2.7 × 1.0 "
Weight	Approx. 85 g / 3.0 oz
Accessories	A clip and a cable
Power Supply	1 × ICR-18500 rechargeable lithium battery





